

# How does a Rubflex Friction VC clutch work?

Our company offers different How does a Rubflex Friction VC clutch work? at Wholesale Price? Here, you can get high quality and high efficient How does a Rubflex Friction VC clutch work?

CB Series, Compatible Model / Part Number 4CB200 at The Eaton Airflex VC series is a line of clutches and brakes specifically designed They feature ventilated friction shoes to permit clutch slippage at

Rubflex VC Clutch and brake features and sizes - Knowledge Rubflex VC products are designed to excel in severe clutching and braking applications on heavy-duty equipment. The threat of large inertia loads and Rubflex (@dalin\_motion) / TwitterRubflex is Global Industrial Clutches&Brakes Provider In China. Our products include Disc clutch, VC clutch, CB clutch, PO clutch, PTO clutch.

Rubflex Friction VC Clutch								
	W MM	Size	V MM	V (mm)	W Inch	V (in)	V Inch	O3 (mm)
<a href="#">26CB525</a> <a href="#">142268KP</a>	-	407097	359 lb-ft <sup>2</sup> ; 15.08 kg·m <sup>2</sup>	32CB525	1201 lb; 544 kg	-	4.00 in; 102 mm	9.70 in; 246 mm
<a href="#">28CB525</a> <a href="#">142269KP</a>	Tapped Holes	-	-	-	-	-	-	-
<a href="#">30CB525</a> <a href="#">142270KP</a>	-	-	-	-	-	-	Eaton- Airflex	-
<a href="#">32CB525</a> <a href="#">142271KP</a>	-	-	6.00 in; 152 mm	15.75 in; 400 mm	-	-	-	-
<a href="#">36CB525</a> <a href="#">142272KP</a>	-	6.00 in; 152 mm	62300 lb-in; 7040 Nm	2.75 in; 70 mm	-	5.40 in; 137 mm	22CB500	-
<a href="#">40CB525</a> <a href="#">142273KP</a>	-	-	1.38 in; 2.25 in	-	-	1.750 thru 2.500	-	4.1 in; 86 mm
<a href="#">45CB525</a> <a href="#">142081KP</a>	-	9.00 in; 229 mm	-	Tapped Holes	160 lb; 72 kg	-	-	-
<a href="#">12CB350</a> <a href="#">104137</a>	-	-	-	-	8.00 in; 203 mm	-	-	-
<a href="#">16CB500</a> <a href="#">104142</a>	9 lb-ft <sup>2</sup> ; 0.38 kg·m <sup>2</sup>	1.25 in; 32 mm	2.56 in; 65 mm	5.69 in; 145 mm	0.81 in; 21 mm	1.50 in; 38 mm	2150 rpm	0.250 in; 6.4 mm
<a href="#">18CB500</a> <a href="#">104144</a>	760000 lb-in; 85870 Nm	+0.000/-0. 010 in; +0. 00/-0.25 mm	52.25 in; 1327 mm	40	-	-	24	7.500 °
<a href="#">20CB500</a> <a href="#">104145</a>	-	-	-	-	-	-	-	6.00 in; 152 mm

<a href="#">22CB500 104147</a>	-	2.563 thru 3.125	-	-	-	14CB400	-	-
<a href="#">24CB500 104148</a>	-	-	-	15 mm	-	165 mm	-	-
<a href="#">26CB525 104149</a>	-	-	2.0 in; 51 mm	-	-	-	0.531 in; 13.5 mm	-
<a href="#">30CB525 104151</a>	1.750 thru 2.500	2.00 in; 51 mm	Eaton- Airflex	-	73 in	-	-	0.531 in; 13.5 mm
<a href="#">32CB525 105472</a>	50.75 in; 1289 mm	4	+0.000/-0. 010 in; +0. 00/-0.25 mm	21160 lb-ft <sup>2</sup> ; 888.7 kg-m <sup>2</sup>	-	4000 in <sup>3</sup> ; 65.6 dm <sup>3</sup>	-	125 E-06 psi/rpm <sup>2</sup> ; 8.63 E-06 bar/rpm <sup>2</sup>
<a href="#">36CB525 105473</a>	-	-	Eaton- Airflex	10 in; 7 in	35 in; 57 in	-	-	-
<a href="#">40CB525 104153</a>	-	580 in <sup>3</sup> ; 9.51 dm <sup>3</sup>	621 lb-ft <sup>2</sup> ; 26.08 kg-m <sup>2</sup>	38.000 in; 965.2 mm	-	-	-	-
<a href="#">45CB525 105474</a>	-	-	2.563 thru 3.125	-	-	1.38 in; 35 mm	-	0.531 in; 13.5 mm
<a href="#">14CB400 105501</a>	-	-	-	-	-	-	2.563 thru 3.125	3.9 in; 99 mm
<a href="#">16CB500 105502</a>	0.48 in; 12 mm	-	3.5 lb; 1.6 kg	4.90 in; 124 mm	8.071 in; 205 mm	8.07 in; 205 mm	-	22.500 °
<a href="#">18CB500 105503</a>	-	-	21.33 in; 542 mm	10	-	23.25 in; 591 mm	-	-
<a href="#">20CB500 105504</a>	-	-	-	-	2.563 thru 3.125	-	-	-
<a href="#">22CB500 105505</a>	555 lb; 251.7 kg	-	27.378/27 .375 in; 69 5.33/695. 40 mm	-	32.75 in; 831.9 mm	285 lb-ft <sup>2</sup> ; 12.0 kg-m <sup>2</sup>	21/32 in; 16.7 mm	16.25 in; 412.8 mm
<a href="#">24CB500 105506</a>	3000 rpm	2.0 lb; 0.9 kg	-	0.307 in <sup>2</sup> ; 1.98 cm <sup>2</sup>	3.00 in; 3.15 in; 76 mm; 80 mm	-	-	1/2-14
<a href="#">26CB525 105507</a>	-	6.50 in; 165 mm	0.75 in; 19 mm	28CB525	Thru Holes	25.00 in; 635 mm	-	-
<a href="#">28CB525 105508</a>	7.76 in; 197 mm	-	-	-	-	1100 rpm; 1700 rpm	-	0.73 in; 19 mm
<a href="#">12CB350 142098K H</a>	23.00 in; 584 mm	360 rpm	16	24.500 in; 622.3 mm	361; 796	2.70 in; 69 mm	4	-
<a href="#">14CB400 142087K H</a>	-	Air Applied	-	-	-	32 lb-ft <sup>2</sup> ; 1.34	-	-
<a href="#">16CB500</a>	-	-	-	-	0.531 in;	-	-	0.75 in; 19

<a href="#">142211KT</a>					13.5 mm			mm
<a href="#">18CB500</a> <a href="#">142264KT</a>	6	-	-	1.38 in; 35 mm	-	-	-	1/4-18 in
<a href="#">20CB500</a> <a href="#">142265KT</a>	-	-	-	-	58 lb-ft <sup>2</sup> ; 2.44 kg-m <sup>2</sup>	-	18.500 in; 469.9 mm	-
<a href="#">22CB500</a> <a href="#">142266KT</a>	22.8 in; 579 mm	104909AB	-	250 x 20	1-11 1/2	-	Eaton-Airflex	3.75 in; 95 mm
<a href="#">24CB500</a> <a href="#">142267KT</a>	-	-	12 lb; 5.4 kg	-	-	-	-	-
<a href="#">26CB525</a> <a href="#">142268KT</a>	446 mm	1000 Nm; 660 Nm; 830 Nm	168 kg	0.6 mm	-	Spring Applied, Electric Release	-	-
<a href="#">28CB525</a> <a href="#">142269KT</a>	-	1.750 thru 2.500	12CB350	-	-	-	-	Air Applied
<a href="#">30CB525</a> <a href="#">142270KT</a>	-	38 lb/ft <sup>2</sup>	-	-	14000 lb-in	-	-	-
<a href="#">32CB525</a> <a href="#">142271KT</a>	1882 lb; 855 kg	1/2-14 NPT	-	854 lb; 388 kg	-	-	-	30.89 in; 785 mm
<a href="#">36CB525</a> <a href="#">142272KT</a>	-	-	-	-	-	-	-	-
<a href="#">40CB525</a> <a href="#">142273KT</a>	2.563 thru 3.125	-	-	Eaton-Airflex	-	-	-	-
<a href="#">16CB500</a> <a href="#">142432D</a> <a href="#">K</a>	0.280 in; 7.1 mm	4	2.38 in; 60 mm	8022 Nm @ 5.5 bar	213; 470	78 gpm; 295.3 dm <sup>3</sup> /min	28.000 in; 711 mm	1.52 in; 39 mm
<a href="#">18CB500</a> <a href="#">142433D</a> <a href="#">K</a>	-	20CB500	Tapped Holes	6.62 in; 168 mm	-	-	-	-
<a href="#">20CB500</a> <a href="#">142434D</a> <a href="#">K</a>	-	-	-	10.50 in; 267 mm	4.00 in; 102 mm	2.812 in; 71.4 mm	-	13300 lb-in; 1500 Nm
<a href="#">22CB500</a> <a href="#">142435D</a> <a href="#">K</a>	1200 rpm	3.73 in; 95 mm	-	-	-	1.13 in; 29 mm	0.124 in <sup>2</sup> ; 0.80 cm <sup>2</sup>	Eaton-Airflex
<a href="#">24CB500</a> <a href="#">142436D</a> <a href="#">K</a>	-	106000 lb-in; 12000 Nm	-	26CB525	8.70 in; 221 mm	-	-	216 lb; 98 kg
<a href="#">26CB525</a> <a href="#">142437D</a> <a href="#">K</a>	-	-	-	-	8.00 in; 203 mm	-	32CB525	-
<a href="#">28CB525</a> <a href="#">142438D</a> <a href="#">K</a>	2.0 A	260 Nm; 330 Nm; 400 Nm	-	-	400 mm	-	-	14 mm
<a href="#">30CB525</a>	-	411863	8.00 in;	-	63 lb-ft <sup>2</sup> ;	Air	1.44 in; 37	-

<a href="#">142439D</a> <a href="#">K</a>			203 mm		2.65 kg·m <sup>2</sup>	Applied	mm	
<a href="#">32CB525</a> <a href="#">142440D</a> <a href="#">K</a>	B2	-	5.80 in; 147 mm	-	3.20 in; 81 mm	22 lb; 10 kg	187 lb; 85 kg	13300 lb·in; 1500 Nm
<a href="#">36CB525</a> <a href="#">142441D</a> <a href="#">K</a>	-	0.3 mm	100 Nm	26 mm	-	-	-	106 mm
<a href="#">40CB525</a> <a href="#">142442D</a> <a href="#">K</a>	3/8-18 in	-	97 lb; 44 kg	87 lb·ft <sup>2</sup> ; 3.65 kg·m <sup>2</sup>	2.50 in; 64 mm	5.30 in; 135 mm	-	-
<a href="#">45CB525</a> <a href="#">142443D</a> <a href="#">K</a>	1.44 in; 37 mm	6.60 in; 168 mm	268 lb·ft <sup>2</sup> ; 11.26 kg·m <sup>2</sup>	C2	14.75 in; 375 mm	3.81 in; 97 mm	252 lb·ft <sup>2</sup> ; 10.58 kg·m <sup>2</sup>	55 lb·ft <sup>2</sup> ; 2.31 kg·m <sup>2</sup>
<a href="#">14CB400</a> <a href="#">105481</a>	130 mm	10 mm	Pintsch Bubenzer	Spring Applied, Electro-Hydraulic Release	190 mm	-	500 mm	325 mm
<a href="#">16CB500</a> <a href="#">105482</a>	-	-	-	-	8	10 in <sup>3</sup> ; 0.17 dm <sup>3</sup>	-	-
<a href="#">18CB500</a> <a href="#">105483</a>	1360 in <sup>2</sup> ; 8772 cm <sup>2</sup>	97.86 kg·m <sup>2</sup>	3.13 in; 79 mm	9.000 °	+0.005/-0.000 in; +0.13/-0.00 mm	-	2330 lb·ft <sup>2</sup>	20
<a href="#">20CB500</a> <a href="#">105522</a>	303 lb·ft <sup>2</sup> ; 12.73 kg·m <sup>2</sup>	-	6.80 in; 173 mm	390 lb·ft <sup>2</sup> ; 16.38 kg·m <sup>2</sup>	Air Applied	411869	-	1093 lb; 495 kg
<a href="#">22CB500</a> <a href="#">105484</a>	0.54 in; 14 mm	-	4290 lb·in; 485 Nm	1200 rpm; 1700 rpm	-	-	-	Eaton-Airflex
<a href="#">24CB500</a> <a href="#">105485</a>	-	142 mm	Pintsch Bubenzer	1.8 mm	450 mm; 550 mm	-	-	-
<a href="#">26CB525</a> <a href="#">105486</a>	4.00 in; 102 mm	0.19 in; 5 mm	3/8-18	0.31 in; 8 mm	17.88 in; 454 mm	-	1800 rpm	-
<a href="#">28CB525</a> <a href="#">105487</a>	-	1112 lb; 504 kg	-	Air Applied	-	6.50 in; 165 mm	-	-
<a href="#">30CB525</a> <a href="#">105488</a>	-	4.75 in; 120.7 mm	-	60541 lb·in; 6720 Nm	4.00 in; 101.6 mm	21/32 in; 16.7 mm	2150 rpm	7-016-200-100-0
<a href="#">20CB500</a> <a href="#">142434D</a> <a href="#">A</a>	-	4.13 in; 105 mm	-	921 Nm	-	-	-	-
<a href="#">22CB500</a> <a href="#">142435D</a> <a href="#">A</a>	17.63 in; 448 mm	-	-	-	-	9.19 in; 233 mm	13.69 in; 348 mm	1000 rpm; 1500 rpm
<a href="#">24CB500</a>	-	-	Eaton-	87 in	1.3 in; 33	-	12CB350	-

<a href="#">142436D</a> A			Airflex		mm			
<a href="#">26CB525</a> <a href="#">142437D</a> A	35 in; 57 in	10 in; 7 in	3.7 in; 94 mm	2.50 in; 64 mm	-	14CB400	1.750 thru 2.500	-
<a href="#">28CB525</a> <a href="#">142438D</a> A	-	8.250 in; 209.6 mm	-	-	14CB400	-	Eaton-Airflex	2230 Nm
<a href="#">30CB525</a> <a href="#">142439D</a> A	-	3.44 in; 84 mm	4290 lb·in	12.47 in; 317 mm	-	-	-	5.250 in; 133.4 mm
<a href="#">32CB525</a> <a href="#">142440D</a> A	-	-	-	-	-	-	-	-
<a href="#">36CB525</a> <a href="#">142441D</a> A	-	-	12.69 in; 322 mm	900 rpm	38	-	38.750 in; 984.3 mm	-
<a href="#">40CB525</a> <a href="#">142442D</a> A	-	6.250 in; 209.6 mm	-	-	-	-	2230 Nm	-
<a href="#">45CB525</a> <a href="#">142443D</a> A	14CB400	2.563 thru 3.125	6	-	-	-	5.22 in; 133 mm	0.531 in; 13.5 mm

Rubflex 20CB500 142265KR For Oil Feild Machinery Hot Except this CB element , we also has VC clutches brakes, Disc clutches brakes and its spare parts, such as friction disc,pressure plate,center plate,

Dalinmotion: HomeDalin products including all kinds of clutch and its accessories:WCB Clutch,ATD Clutch,PO Clutch,PTO Clutch, VC Clutch,CB Clutch.Mainly used on driving or Cheap Price Eaton Airflex Pneumatic Clutch Type CB 142267Henan Dalin is a professional eaton airflex pneumatic clutch type cb 142267 factory in and other functions to meet the most demanding work requirements.

new 12cb350 single flange pneumatic clutch/brake element Henan Dalin is a professional new 12cb350 single flange pneumatic clutch/brake Working. pressure. Mpa. Friction. wheel. norminal. diameter. ?1millimeter.